

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: APOSTOLIDIS TRADING SA

Supplier's address: ΑΠΟΣΤΟΛΙΔΗΣ ΑΕΒΕ, ΠΑΛΑΜΗΔΙΟΥ 15, 18545 ΠΕΙΡΑΙΑ ΠΕΙΡΑΙΑΣ ΑΤΤΙΚΗΣ, EL

Model identifier: GX538NW

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	GX53		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No


Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	8	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	700 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P_{on}), expressed in W	8,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		


parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,376 0,378	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	0	Survival factor	0,96	
the lumen maintenance factor	0,97			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,95	Colour consistency in McAdam ellipses	2	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,3	Stroboscopic effect metric (SVM)	0,2	

(a) '-': not applicable;

(b) '-': not applicable;



Model placed on the Union market from 01/09/2021



EPREL registration number: 974377

<https://eprel.ec.europa.eu/qr/974377>

Supplier: APOSTOLIDIS AEVE (Importer)

Website: www.acalight.gr

Customer care service:

Name: ΑΠΟΣΤΟΛΙΔΗΣ ΑΕΒΕ

Website: www.acalight.gr

Email: sales12@acalight.gr

Phone: +30 2104203846

Address:

ΠΑΛΑΜΗΔΙΟΥ 15

18545 ΠΕΙΡΑΙΑΣ

Greece